

HIGH-PERFORMANCE BALL VALVES FOR STEAM SERVICE

Jamesbury high-performance ball valves are ideal for use in a wide range of industrial, commercial and institutional steam applications, including both saturated and superheated steam. They are available in sizes 1/4" through 20" (DN 8-500) with a variety of end connections, pressure ratings, and seat materials all possessing unique features common to Jamesbury brand valves.

FEATURES

- Proven flexible lip seat design in polymeric seated valves assures long lasting positive shut-off.
- Operation is always easy, even when valves are cycled infrequently.
- Minimum maintenance requirements reduce down-time and lower costs.
- High flow capacity with minimum pressure drop.
- Quarter turn operation for stem seal integrity.
- Continuous position indication.
- Easy to automate.

PRESSURE RATINGS

Maximum steam pressure ratings of polymeric seats in ball valves used for on-off service are shown in Table 1. Flanged ball valves, ANSI rated Eliminator™ and 4000 Series conform to standard Class valve ratings published in ANSI B16.34. Throttling applications for polymeric seated valves should be limited to pressure drops of 50 psi (3.5 bar) or less, due to the erosive effect of steam on a partially open ball valve. Any valve used in steam service should have 316 stainless steel ball and stem.

Valve Type	Valve Size		Seat Material	Differential Max. Pressure	
	Inches	DN		psi	bar
All Types	1/4-2	6-50	PTFE (T)	150	10
2000, 3000	1/4-2	6-50	Filled PTFE (M)	250	17
6F, 3A, 3C	1/2-2	15-50	Filled PTFE (M)	250	17
4000	1/2-2	15-50	Filled PTFE (M)	250	17
			<i>XTREME™ (X)</i>	475	33
			PEEK® (L)	475	33
			PFA (B)	225	15
Eliminator™	1/4-2	6-50	Filled PTFE (M)	250	17
			<i>XTREME (X)</i>	475	33
			PEEK (L)	475	33
530S, 5300	1/2-2	15-50	Filled PTFE (M)	250	17
			<i>XTREME (X)</i>	475	33
			PEEK (L)	475	33
			PFA (B)	180	12
5150	1/2-2	15-50	Filled PTFE (M)	200	14
			<i>XTREME (X)</i>	200	14
			PEEK (L)	200	14
			PFA (B)	180	12
All 5000	14-20	350-500	Filled PTFE (M)*	150	10
6300	3/4-1-1/2	20-40	Filled PTFE (M)	250	17
			<i>XTREME (X)</i>	475	33
			PEEK (L)	475	33
			PFA (B)	180	12
6150	3/4-1-1/2	20-40	Filled PTFE (M)	250	17
			<i>XTREME (X)</i>	200	14
			PEEK (L)	200	14
			PFA (B)	180	12
All 6000	14-20	350-500	Filled PTFE (M)*	150	10
7150	3-6	80-150	Filled PTFE (M)	200	14
			<i>XTREME (X)</i>	200	14
			PEEK (L)	200	14
			PFA (B)	180	12
7150	8-12	200-300	Filled PTFE (M)	190	13
730S, 7300	3-6	80-150	Filled PTFE (M)	250	17
			<i>XTREME (X)</i>	350	24
			PEEK (L)	350	24
			PFA (B)	180	12
730S, 7300	8-12	200-300	Filled PTFE (M)	250	17
9150	2-4	50-100	Filled PTFE (M)	200	14
			<i>XTREME (X)</i>	200	14
			PEEK (L)	200	14
			PFA (B)	180	12
9150	6-12	150-300	Filled PTFE (M)*	150	10
9300	2-4	50-100	Filled PTFE (M)	250	17
			<i>XTREME (X)</i>	350	24
			PEEK (L)	350	24
			PFA (B)	180	12
9300	6-12	150-300	Filled PTFE (M)	250	17

* PTFE (T) seats may be used but filled PTFE (M) are recommended.

HOW TO ORDER

Ordering instructions, along with dimensions and other specifications for Jamesbury ball valves suitable for steam service, can be found in the Bulletins listed to the right.

Valve Type	Bulletin
Style A screwed end valves	B100-1
Eliminator screwed end valves	B101-2
Series 6F full port screwed end ball valves	B101-3
Series 2000 Clincher® screwed end valves	B102-1
Type 300 screwed end (brass) valves	B103-1
Series 3000 screwed end valves	B104-1
Series 4000 3-piece screwed, socket weld, and butt-weld end valves	B105-1
Series 3A/3C 3 piece ball valves	B105-4
Series 9000 ANSI Class 150 and 300 full port flanged ball valves	B107-1
Series 7000 ANSI Class 150 and 300 flanged ball valves	B107-1
Series 5000 ANSI class 150 and 300 flanged ball valves 1/2" - 2" (DN 15-50)	B107-1
12" - 20" (DN 300-500) trunnion design	B107-1
Series 6000 ANSI class 150 and 300 full port flanged ball valves 3/4" - 1 1/2" (DN 20-40)	B107-1
12" - 20" (DN 300-500) trunnion design	B107-1

Installation Instructions, Maintenance and Operation

IMO's (Installation, Maintenance, and Operating instructions) or AMI's (Assembly, Mounting, and Installation instructions) are shipped with the products. Additional copies of these instructions are available. Call your local Metso Automation Distributor, or visit our web site.

Metso Automation, Field Systems Division

Europe, Levytie 6, P.O.Box 310, 00811 Helsinki, Finland. Tel. int. +358 20 483 150. Fax int. +358 20 483 151

Europe (UK), 8 Pipers Wood Industrial Park, Waterlooville, Hampshire PO7 7XU UK. Tel. int. +44 (0)23 9223 8500. Fax int. +44 (0)23 9223 8510

North America, 44 Bowditch Drive, P.O.Box 8044, Shrewsbury, Massachusetts, 01545-8044 USA. Tel. int. +1 508 852 0200. Fax int. +1 508 852 8172

North America, 3100 Medlock Bridge Road, Suite 250, Norcross, GA 30071, USA. Tel. int. +1 770 446 7818. Fax int. +1 770 242 8386

Latin America, Av. Central, 181- Cháracas Reunidas, 12238-430, São Jose dos Campos. Tel. int. +55 12 335 3500. Fax int. +55 12 335 3535

Asia Pacific, 501 Orchard Road, #05-09 Wheelock Place, 238880 Singapore. Tel. int. +65 735 5200. Fax int. +65 735 2955

www.jamesbury.com

